




EAM SERIES END-STACKABLE TYPE



■ FEATURES

- End stackable for standard 0.1" integrated circuit pitch
- Molded 0.3" integrated circuit packing outline allowing automatic insertion
- Smaller size makes better heat convection during PC board reflow wave soldering
- Top tape sealed to withstand wave soldering, board washing
- All plastics are UL 94V-0 grade fire retardant
- Twin contacts designed to ensure stable contact
- Gold plated contact to ensure low contact resistance and Tin plated terminal to prevent contamination during soldering
- RoHS Compliant
- Halogen Free series available

■ APPLICATIONS

- Numerical setting for computer terminal equipment
- Price setting for vending machines
- Programming for game machines
- Programming for industrial equipment and measuring instruments

■ SPECIFICATIONS


1.ELECTRICAL

● Contact rating	switching	25mA, 24VDC
	non-switching	100mA
● Contact resistance	initial	50mΩ Max.
	after life test	100mΩ Max.
● Insulation resistance		1000MΩ Min. at 100VDC
● Dielectric strength		500VDC Min. for 60 seconds
● Capacitance between adjacent switches 5pF Max.		


2.MECHANICAL and ENVIRONMENTAL

● Temperature rating	
operating	-40°C to +85°C
storage	-40°C to +85°C
● Operation force	800g Max.
● Mechanical life	2000 operations
● Humidity	95 %RH, 40°C for 96 Hrs.
● Vibration	10Hz-55Hz-10Hz for 6 Hrs.
● Solderability	After flux 245±5°C for 5±1 seconds
● Resistance to soldering heat	Solder bath:260±5°C for 5±1 seconds.

■ PART NUMBERING SYSTEM



■ CONSTRUCTION





■ OPTIONS

- 1.Special marking is available
- 2.Two kinds of pitch available

3.Extended Actuator

4.Tape Sealed

Actuator	Pitch(mm)	
	Standard	Option
L	8.50	7.62
E	7.62	8.50



■ DIMENSIONS AND CIRCUITRY

EAM SERIES

Dimension A

UNIT: mm(inch)



Positions	1	2	3	4	5	6	7	8	9	10	12
A	2.50 (0.098)	5.04 (0.198)	7.58 (0.298)	10.12 (0.398)	12.66 (0.498)	15.20 (0.598)	17.74 (0.698)	20.28 (0.798)	22.82 (0.898)	25.36 (0.998)	30.43 (1.198)

NOTE: 1 pole switches have the "ON" printing.

NOTE: 2-12 pole switches have the "●N" printing.


NOTE: 1&2&3 pole switches don't have the "ECE" Mark.

CIRCUIT DIAGRAM



(L)TYPE

(E)TYPE



P.C.B. LAYOUT (TOP VIEW)

